

RECEIVED PTO

25 APR 2005

PCT/GB 2003 / 004414



INVESTOR IN PEOPLE



PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 17.NOV 2003


WIPO PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.




Signed

Stephen Hordley

Dated

24 October 2003



The
**Patent
Office**

1/77

01NDV02 E760077-1 D03052
P01/7700 0.00-0225359.9
The Patent Office

Cardiff Road
Newport
Gwent NP10 8QQ

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference

A30191

2. Patent application number
(The Patent Office will fill in this part)

0225359.9

31 OCT 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

**BRITISH TELECOMMUNICATIONS public limited company
81 NEWGATE STREET
LONDON, EC1A 7AJ, England
Registered in England: 1800000**

Patents ADP number (if you know it)

1867002

6300388001

If the applicant is a corporate body, give the country/state of its incorporation

UNITED KINGDOM

4. Title of the invention

DATA ACCESSION PROCESS

5. Name of your agent (if you have one)

LIDBETTER, Timothy Guy Edwin

"Address for Service" in the United Kingdom to which all correspondence should be sent (including the postcode)

**BT GROUP LEGAL SERVICES
INTELLECTUAL PROPERTY DEPARTMENT
HOLBORN CENTRE
120 HOLBORN
LONDON, EC1N 2TE**

Patents ADP number (if you know it)

1867001

7980311001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day/month/year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

YES

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

(See note (d))

9. Enter the number of sheets for any of the following items you are filing with this form.
☐ not count copies of the same document

Continuation sheets of this form

Description 8

Claim(s) 2

Abstract 1

Drawing(s) 6 ab

10. If you are also filing any of the following, state how many against each item

Priority Documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) **YES**

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.
Signature(s) _____ Date: _____

31 October 2002

LIDBETTER, Timothy Guy, Authorised Signatory

2. Name and daytime telephone number of person to contact in the United Kingdom

Samantha Radley

020 7492 8146

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.

Write your answers in capital letters using black ink or you may type them.

If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.

If you have answered 'Yes' Patents Form 7/77 will need to be filed.

Once you have filled in the form you must remember to sign and date it.

For details of the fee and ways to pay please contact the Patent Office.

20151.000

DUPLICATE

DATA ACCESSION PROCESS

This invention relates to the accession of latency dependant traffic like voice and video conferencing data from remote internet based servers and applications. In
5 such traffic it is important to minimise delay times as users are interacting in real time.

Currently, if a user having a high bit rate (2Mb/s) ADSL (asymmetric digital subscriber loop) connection attempts to send or receive real time data over the internet the results may not be satisfactory as the data packets can get delayed due
10 to congestion and contention for capacity with other users over shared intermediate links. This delay is variable as it depends on what other traffic is present from moment to moment. It is possible to alter the underlying network to prioritise real time traffic – see for example International Patent Application WO99/12329, but this requires changes to the core Internet Protocol (IP) network.

15 The concept of using multiple virtual connections and access connections to support improved throughput is already established and implemented in the form of Inverse Multiplexing for ATM (IMA) (*ATM-Forum AF-PHY-0086.0010*): for internet access the end user would get a single IP address and the access server would reassemble the data into one stream for routing across the internet. Note the access
20 server is the gateway between the connection orientated ATM access network and the IP routed core. Therefore there would be no benefit if the bottleneck is in fact between the access server and the application being accessed across the internet.

Most access networks have the capability to allow an end user, if he so chooses, to gain access several times simultaneously, using the same or different
25 internet service providers. Each time the user logs on he gets another IP address. To the core IP network these addresses all appear to be separate users. When it is heavily loaded, the core network divides its bandwidth up equally between the addresses contending for access, so a user who has logged on three times will get three times as much bandwidth as a user logged on only once. The mechanism to log
30 on a plurality of times could be multiple asynchronous transfer mode (ATM) permanent or switched virtual connections (PVCs or SVCs), or the PPPoE (Point to Point Protocol over Ethernet). A web based server or peer application receiving requests for a particular stream from three separate IP address will expect the

requests to have come from three different users and act accordingly. For example a video conference bridge will add three new users to the requested conference and relay the video / voice data received from each one to the other two. Note that the signals are duplicates of each other, so unless additional measures are taken, which
5 are the subject of the applicant's co-pending application having applicant's reference A30190 and filed on the same date as the present application, the additional bandwidth does not allow the user to obtain convey any additional information.

Although each data stream will be the same, the variable delay means that different connections will be closest to real time at different times. If the initially
10 optimum connection is subsequently swamped by a number of large packets, later packets in that stream may be delayed by more than their equivalents in another stream.

According to the invention, a user terminal for accessing data from a web based server or peer application over a distributed information network, is provided
15 with means for generating a plurality of access requests for a plurality of duplicate series of packet data from one source over a plurality of routes, each series comprising one instance of each packet of an ordered set of packets, means for accepting the first instance to be received of each packet in the series, and means for assembling the accepted packets into a complete series.

20 Another aspect of the invention provides a method of accessing data from a internet application over a distributed information network, wherein a plurality of access requests are generated for a plurality of duplicate series of packet data from one source over a plurality of routes, each series comprising one instance of each packet of an ordered set of packets, and wherein the first instance to be received of
25 each packet in the series is accepted, and the accepted packets are assembled into a complete series.

This invention relies on the user terminal and source server communicating with each other using real time data, to have a choice of routes to send the data. The sending application transmits the real time data over two or more routes
30 simultaneously. The receiving application then has an improved chance of receiving each packet within an acceptable time, as the probability of the same packet being extensively delayed over all routes is relatively small.

In a preferred arrangement, the user terminal has means for determining the packet delay and variation over a first route and, if the packet delay and variation exceed acceptable limits in the access network, generating a request for access by means of one or more further routes. This allows the end user to choose to log on
5 one or more times to one or more internet service providers. Each time he logs on, he is given another IP (Internet Protocol) address. The core IP network responds as if each address is a separate user.

With minor changes most access networks have the capability to allow an end user, if he so chooses, to gain access several times simultaneously, using the
10 same or different internet service providers. Each time the user logs on he gets another IP address. To the core IP network these addresses all appear to be separate users.

If the user logs on several times to the same Internet Service Provider (ISP) he will be allocated addresses on the same end-routed domain so the data is very
15 likely to take a similar route over the internet, reducing the likely benefits of diversity. However, if the user logs on to three different ISPs there is a far greater chance that the data will take different routes across the internet and so be subject to different delay profiles.

The mechanism to log on multiple times could be any existing system such
20 as multiple Asynchronous Transfer Mode (ATM) Permanent or Switched Virtual Connections (PVCs or SVCs), or the PPPoE (Point to Point Protocol over Ethernet).

The application which is to send data to the end user will register two or more addresses to which to send duplicate data. The receiving application is arranged to use the first packet that is received and discard the duplications when they are
25 subsequently received. Note that instances of subsequent packets from each route may be delivered in a different order from the order in which the instances of the first packet arrive. Thus one packet stream may deliver the first packet of the stream before another packet stream does so, but the second packet of that stream may be delayed to such an extent that it arrives after both the (duplicate) first packet and the
30 second packet of another stream are delivered. For each packet, the first instance to arrive at the user terminal is assembled, so that an aggregate data stream is generated having lower delay, and lower delay variation, than any of the individual streams could have generated on its own.

It is possible that packet series delivery on one access route has fallen substantially behind others, so that no packets are being used from that route. In that case, it may be desirable to make an adjustment to the delivery process on that access route. This may be simply be closing the connection, thereby saving on
5 bandwidth, and therefore cost if payment is made by time or number of packets delivered. Alternatively the access server may be requested to omit a specified number of packets (which have already been received over one of the other duplicate routes)

Packets may have been omitted or corrupted in one or more of the packet
10 streams. It is therefore possible for the first instance of a packet to arrive on one route out of sequence, that is to say before the arrival (over another route) of the first (uncorrupted) instance of the packet that should precede it. If accuracy is important, the out of sequence packet may be buffered until the arrival of the first instance of the packet that should precede it, so that it can be assembled in its
15 correct place in the output sequence. However, in some forms of real-time signalling, such as video conferencing, speed takes priority over accuracy. In such circumstances the out-of-sequence packet may be output immediately it arrives over a first route, all instances of the packet that should have preceded (including the first instance) it being disregarded when they eventually arrives over another route.

20 If additional bandwidth is required on one or more of the channels, the present invention may be used in combination with that of the applicant's co-pending application A30190, previously referred to. For example using six feeds (IP Addresses), the stream may be split into two to double the bandwidth, and then these two streams are then each duplicated three times to reduce delay according to
25 the present invention)

Embodiments of the invention will now be described, by way of example, with reference to the drawings in which:

Figure 1 is a schematic illustration of a prior art Single ISP Connection Service

30 Figure 2 is a schematic illustration of the connection of three switched virtual connections (SVCs) to three Internet Protocol (IP) Addresses;

Figure 3 is a schematic illustration of a system operating according to the invention, with duplicated data streaming.

Figure 4 is a flow chart illustrating the method of operation of one embodiment of the invention.

Figure 5 is a flow chart showing one method of assembly of the incoming bit streams

5 , Figure 6 is a flow chart showing an alternative method of assembly of the incoming bit streams

In all these figures, data is shown in one direction only. It will be appreciated that for applications like video conferencing there would normally be similar streams in the reverse direction.

10 As shown in the conventional system of Figure 1, a single permanent virtual circuit (PVC) 10 is set up between the user terminal 1 of an ADSL user, and the access server 11. The access server 11 terminates the PVC 10 and the Point to Point Protocol (PPP) (12) signalling encapsulated onto the PVC. It also gives the end user terminal 15 an IP address 1X to enable it to connect to the internet (shown generally at 14), and send data to any other internet application, for example a video conferencing application 17 (Figure 3).

With a switched virtual circuit (SVC) ADSL multiplexer (DSLAM) 20 the end user terminal 15 can connect simultaneously to multiple access servers 21, 22, 23. Figure 2 shows the user logged on to three different internet service providers. Again using PPP the user is given a unique routable IP address 21X, 22Y, 23Z for each connection. The increased number of connections marginally increases the contention level (the number of individual IP addresses attempting to access data), which in turn may affect the data rate on each channel at busy times.

For real time data, the time the data takes to traverse the network, known as the latency or "delay" of the network, is very important. The latency of satellite systems is significantly worse than other systems because of the extra distance the data has to travel. (The round-trip distance to a geostationary satellite is approximately 0.25 seconds.) If the data were to be split and different parts of it sent over different routes, the process of storing the retrieved data until it had all been received would result in the latency of the transmission being dictated by that of the poorest service provider.

The system shown in Figure 3 avoids this problem by requesting the same data several times. This may appear to be an inefficient use of resources, in that data

is duplicated. However, the invention merely uses some of the capacity available to the user minimise delay rather than to optimise some other characteristic such as picture quality.

The internet application sending the data, for example a video conferencing application 17, sends the data out on three different paths 21, 22, 23. The latencies of networks vary dynamically due to variable traffic loading. Consequently the sequenced data frames may be received at different delays and it will not always be any given path 21, 22, 23 that is quickest. As will now be described with reference to Figure 4, the receiving application 15 processes the sequenced data frame (packet) that is received first and ignores the same data frame when subsequently received via another route. Figure 3 also shows illustrative data streams operated according to the invention.

As shown in Figure 4, the user terminal 15 first logs on to one or more ISPs 21, 22, 23 and gets a user address X, Y, Z for each, (step 40). It then requests access to the internet application 17 over one of the ISP networks 21 (step 41). The requested data is returned from the internet application 17 to the user terminal 15, and the packets are reassembled into a data stream 16 (step 43). The user terminal 15 then determines whether the rate at which the data is arriving is acceptable (step 44). If it is acceptable it is delivered to the user by way of a display or other human interface (step 47). If the rate is not acceptable, a request is made to the same internet application 17, using a different ISP 22 (step 45). (Logging on to the second ISP may take place at this point, or at the same time as the first ISP as shown in Figure 4). The same data is therefore now sent to the user terminal 15 from the internet application 17 by two different routes 21, 22. This cycle is continued until an acceptable rate is achieved (or the user runs out of available ISPs to use).

The assembly step 43 will be described in more detail, with reference to Figures 5 and 6. Some of the steps in Figures 5 and 6 are similar: where this is the case they are referenced with the same two final digits.

Each packet of a stream has a position value R, which identifies where it should come in the stream. In the present invention, a plurality of identical streams are being delivered and there should therefore be a plurality of instances of packets having each value R. The user terminal should identify and use the first instance of each value of R and discard the rest. The user terminal keeps a running total N of the

position value R which the user terminal 15 is expecting – in other words the highest value of R so far received is N-1. As shown in Figures 5 and 6, this is initially set at a value of 1 (step 431/ 631).

When a packet is received, (step 432/632) the position value R is compared
5 with the running total N (step 433/633). If R and N are equal, signifying that this is the first instance of that packet to arrive, the packet is added to the output stream (step 435/635) and the running total is incremented by 1 (step 436/636). If the position value is less than the running total, this signifies that a packet having the same position value (and therefore a duplicate of the present packet) has previously
10 been received, and this packet can be discarded (step 439/639).

In the example shown in Figure 3, the first packet is delayed by different amounts in the paths 21, 22, 23, and the user terminal 15 receives it first on path 21 (packet 1) and assembles it as the first element of an output stream 16. Packets 1', 1'', arriving later on the other two paths, are redundant and disregarded. The second
15 and third packets (packets 2,3) on path 21 also arrive before their duplicates (2', 3', 2'', 3'') on the other paths 22, 23. However, the fourth packet (4) has its journey through the path 21 delayed, and the first instance of this packet to arrive is instead the packet 4'' on path 23. This is then added to the assembled output stream 16. Similarly, the fifth packet is seen first on the path 23 (packet 5'') and is added to the
20 output stream 16. Duplicate packets (4, 4', 5, 5') are again disregarded when they eventually arrive.

In the example of Figure 3, path 23 now also experiences a delay, and path 21 has not yet recovered from the earlier delay, so the first instance of packet 6 to arrive is that on the remaining path 22 (packet 6'), and this is duly added to the
25 output stream, packets 6, 6'' being disregarded when they arrive.

The end user 15 therefore gets the lowest delay possible from any of the three networks.

It should be understood that data streams in practice include thousands of individual packets, and the change in relative delay between one path and another is
30 likely to occur on longer timescales than the one or two packets shown here.

On occasion packets are corrupted, lost altogether, or arrive in the wrong order, as a result of variations in switching delay even over the same virtual connection. This can result in a packet arriving which is intended for later in the

sequence than the one that is expected. In other words, the position value R is greater than the running total N . Figures 5 and 6 illustrate two different ways of handling such packets in such a situation.

In Figure 5, should a packet arrive out of sequence, its position value R' ,
5 when checked (step 433) will be found to be greater than the running total N . It is nevertheless added to the output stream 16, and the running total N incremented to the position value of the following packet ($R' + 1$). This means that all instances of the packet that had been expected (which has position value R , ($R < R'$), will now be discarded (step 439). This arrangement ensures that corrupted packets do not delay
10 the output stream, but loses some accuracy because of the omitted packets.

In the arrangement of Figure 6, in which steps similar to those of Figure 4 are given the same reference numerals incremented by 200, if the position value R' is found to be higher than the running total N the packet is added to a buffer (step 634) instead of the output stream 16. When a subsequent packet is added to the output
15 stream 16 (step 635) and the running total incremented (step 636), a check is made to see if the next packet (having a position value R equal to the incremented running total) is already present in the buffer (step 637). If it is already buffered it is added to the output stream (step 635) without the need to wait for a second instance of the packet to be delivered. More than one buffered packet may be delivered in this way
20 before the next packet arrives (step 632). This arrangement allows greater accuracy than that of Figure 4, without losing all the advantages of speed that the process of Figure 4 enjoys.

CLAIMS

1. A user terminal for accessing data from a internet application over a distributed information network, provided with means for generating a plurality of access requests for a plurality of duplicate series of packet data from one source over a plurality of routes, each series comprising one instance of each packet of an ordered set of packets, means for accepting the first instance to be received of each packet in the series, and means for assembling the accepted packets into a complete series.
 2. A terminal according to claim 1, comprising means for determining the packet delay and variation over a first route and, if the packet delay and variation exceed acceptable limits in the access network, generating a request for access by means of one or more further routes.
 3. A terminal according to claim 1 or 2, comprising means for identifying an access route on which packet series delivery has fallen substantially behind others, and means for requesting an adjustment to the delivery process on that access route.
 4. A terminal according to any preceding claim, comprising means for detecting the arrival of the first instance of a packet out of sequence, and means for buffering the said out of sequence packet until the first instance of any packets that should have preceded it are received.
 5. A terminal according to any of claims 1 to 3, comprising means for detecting the out of sequence arrival of the first instance of a packet, and means for disregarding the subsequent arrival of all instances of any packets that should have preceded the out of sequence packet.
 6. A method of accessing data from a internet application over a distributed information network, wherein a plurality of access requests are generated for a plurality of duplicate series of packet data from one source over a plurality of routes, each series comprising one instance of each packet of an ordered set of packets, and
-

wherein the first instance to be received of each packet in the series is accepted, and the accepted packets are assembled into a complete series.

7. A method of accessing data from a internet application over a distributed information network, wherein initially a first access request is made for a series of data packets to be received over a first route, the packet delay and variation of packets received over the first route is measured and, if the packet delay and variation exceed a predetermined limit, one or more requests for duplicate series of data packets are obtained according to the method of claim 6.

8. A method according to claim 6 or claim 7, wherein the duplicate series of packets are obtained using different access servers.

9. A method according to claim 6, 7 or 8, wherein if packet series delivery on one access route has fallen substantially behind others, an adjustment to the delivery process is made on that access route.

10. A method according to claim 6, 7, 8, or 9, wherein if the arrival of the first instance of a packet is out of sequence, the said out of sequence packet is buffered until the first instance of any packets that should have preceded it are received.

11. A method according to any of claims 6, 7, 8 or 9, wherein if the arrival of the first instance of a packet is out of sequence, all instances of any packets that arrive subsequently but should have preceded the out of sequence packet are disregarded.

ABSTRACT
DATA ACCESSION PROCESS

A user terminal (15) accesses data from an internet application (14) over a distributed information network such as the Internet (17), by making a plurality of access requests for a plurality of duplicate series of packet data (1,2,3,.....; 1',2',3',.....; 1'', 2'', 3'',) from the same internet application (14), each series comprising one instance of each packet of an ordered set of packets 1,2,3,4,5,6. The first instance to be received of each packet in the series (1,2,3,4'',5'',6') is accepted, and the accepted packets are assembled into a complete series (16). This ensures that delays on any one link (21, 22, 23) do not delay the receipt of the message.

Figure 3

15






Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6

PCT Application
GB0304414

